



EYE LED square




EYE LED square

er et ledelys for innfelt montasje. Kommer i flere versjoner for korridor og åpne områder. **EYE LED square** har LED lyskilde og er laget i rustfritt stål. Monteres i tak. For valg av rett armatur se avstandstabeller. **EYE LED square** leveres som lavvoltage sentralisert løsning.


Tekniske spesifikasjoner:

Materiale	Rustfritt stål
Mål	80 x 80 x 47 mm
Vekt	390 gram
Montering	Innfelt i tak
Leseravstand	-
Lyskilde	1, 2 eller 3 watt LED
Batteri	-
Driftsspenning	FZLV 48VDC
Kapslingsgrad	IP20
Temperatur	0°C - 40°C



L1 – avstand fra vegg til første armatur
 L2 – avstand mellom armatur
 h – høyde til tak

EYKC – optikk for korridor




h [m]	L1	L2
2,50	6,0	14,0
3,00	6,0	15,0
3,50	6,5	16,0
4,00	6,5	17,0
4,50	7,0	18,0
5,00	7,0	17,5
6,00	4,5	12,0

h [m]	L1	L2
2,50	7,0	17,0
3,00	7,5	18,0
3,50	8,0	20,0
4,00	8,0	21,0
4,50	8,5	22,0
5,00	8,5	23,0
6,00	9,0	24,5

h [m]	L1	L2
2,50	7,5	18,0
3,00	8,0	19,5
3,50	9,0	21,0
4,00	9,5	22,5
4,50	10,0	24,0
5,00	10,5	25,0
6,00	10,5	27,0

EYKR – with optics for escape route



EYKR 1W (140lm) min. 1lx

h [m]	L1	L2
2,50	5,0	13,0
3,00	6,0	14,0
3,50	7,5	16,0
4,00	7,0	15,5


EYKR 2W (260lm) min. 1lx

h [m]	L1	L2
2,50	6,5	14,5
3,00	7,0	16,0
3,50	8,0	18,0
4,00	8,5	19,0
4,50	9,0	21,0
5,00	9,5	22,0
6,00	9,5	22,5

EYKR 3W (350lm) min. 1lx

h [m]	L1	L2
2,50	7,0	15,5
3,00	7,5	17,5
3,50	8,5	19,0
4,00	9,0	20,5
4,50	10,0	22,5
5,00	10,5	24,0
6,00	10,5	24,5

EYKO - with optics for open area



EYKO 1W (135lm) min. 0,5lx

h [m]	L1	L2
2,50	2,5	13,0
3,00	1,5	12,0
3,50	2,0	12,5
4,00	2,0	12,0
4,50	2,0	12,0
5,00	2,0	12,0
6,00	2,0	10,5

EYKO 2W (260lm) min. 0,5lx


h [m]	L1	L2
2,50	4,5	14,5
3,00	4,0	13,5
3,50	4,0	15,0
4,00	3,0	16,5
4,50	2,5	17,0
5,00	3,0	16,5
6,00	3,5	16,0

EYKO 3W (350lm) min. 0,5lx

h [m]	L1	L2
2,50	5,0	16,5
3,00	5,0	16,0
3,50	4,5	17,5
4,00	5,0	18,0
4,50	5,0	18,0
5,00	4,0	19,0
6,00	4,0	18,0



EYKU – with universal optics



EYKU 1W (150lm) min. 0,5lx

h [m]	L1	L2
2,50	3,0	7,0
3,00	3,5	7,5
3,50	3,5	8,5
4,00	4,0	9,0
4,50	4,0	10,0
5,00	4,0	10,0
6,00	4,0	9,5

EYKU 2W (270lm) min. 0,5lx

h [m]	L1	L2
2,50	3,5	7,5
3,00	3,5	8,0
3,50	4,0	9,0
4,00	4,5	10,0
4,50	4,5	11,5
5,00	5,0	12,0
6,00	5,5	13,0

EYKU 3W (390lm) min. 0,5lx

h [m]	L1	L2
2,50	3,5	8,0
3,00	4,0	9,0
3,50	4,0	10,0
4,00	4,5	10,0
4,50	5,0	11,5
5,00	5,5	12,5
6,00	6,0	14,0

Art.nr.	Beskrivelse	Batteri / spenning	System
9151084	EYE LED SQUARE EYKC asym. 1W LED IP20 FZLV2	48VDC	Sentralisert
9151085	EYE LED SQUARE EYKC asym. 2W LED IP20 FZLV2	48VDC	Sentralisert
9151086	EYE LED SQUARE EYKC asym. 3W LED IP20 FZLV2	48VDC	Sentralisert
9151087	EYE LED SQUARE EYKO sym. 1W LED IP20 FZLV2	48VDC	Sentralisert
9151088	EYE LED SQUARE EYKO sym. 2W LED IP20 FZLV2	48VDC	Sentralisert
9151089	EYE LED SQUARE EYKO sym. 3W LED IP20 FZLV2	48VDC	Sentralisert
9151090	EYE LED SQUARE EYKR asym. 1W LED 140 lm IP20 FZLV2	48VDC	Sentralisert
9151091	EYE LED SQUARE EYKR asym. 2W LED 260 lm IP20 FZLV2	48VDC	Sentralisert
9151092	EYE LED SQUARE EYKR asym. 3W LED 350 lm IP20 FZLV2	48VDC	Sentralisert
9151093	EYE LED SQUARE EYKU sym. 1W LED 150 lm IP20 FZLV2	48VDC	Sentralisert
9151094	EYE LED SQUARE EYKU sym. 2W LED 270 lm IP20 FZLV2	48VDC	Sentralisert
9151095	EYE LED SQUARE EYKU sym. 3W LED 390 lm IP20 FZLV2	48VDC	Sentralisert

